

VI-POESWITCH-4



Key Features:

- Layer two commercial switch.
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards.
- MAC auto study and aging, MAC address capacity is 1K.
- RJ45 port supports 10/100 Mbps self-adaptation, supports IEEE802.3af and IEEE802.3at power supply standards.
- Supports MDI/MDIX self-adaptation.
- Metal enclosure.
- Supports DC 48V-57V power supply.
- Supports wall-mount installation.
- Supports anti-theft lock hole.

SPECIFICATIONS

Model Number	VI-POESWITCH-4
Ethernet Port	1*10/100 Base-T 4*10/100 Base-T (PoE power supply) Embedded LINUX
PoE Power Consumption	Port1 ≤60W, Port 2-4≤30W, Total ≤60W
PoE PIN Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
PoE Power Management	Support
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	1Gbps
Packet Forwarding Rate	744Kpps
Packet Buffer Memory	448Kb
MAC Table Size	1K
Flow Control	Enable
Application Humidity	5% ~ 95%
Power	DC48~57V power adapter
Lightning Protection	Common Mode 2KV Differential Mode 1KV
ESD Protection	Air Discharge 8KV Contact Discharge 6KV
Working Temperature	-10°C ~55°C
Weight	290g
Dimension(W×D×H)	130mm × 85mm × 26mm