



LTE700 HG 5 K (Single)

Art. Number 108073



- LTE Protected
- Tool free assembly - Quick lock dipole and reflector
- Strong, rugged construction
- F-Connector dipole housing
- Excellent F/B ratio and performance across the whole UHF band

Technical Specifications

ORDER INFORMATION

EAN Number 5702661080739

CHARACTERISTICS

Antenna use outdoor
Polarization vertical or horizontal

FREQUENCY RANGE

Band UHF
Channels 21...48
Frequency range | MHz 470-694 MHz
LTE protection @ 700Mhz

GAIN

Gain | dBi 9,5-14.5 dBi
Gain @ 474 MHz (Ch. 21) | dBi 9,5-14.5 dBi

ELECTRICAL

Front to back ratio - horizontal | dB 22 dB
Impedance | Ω 75 Ω

CONNECTORS

Connector Type 1 x F connector, 75 Ohm

MECHANICAL

Elements 32



TRIAX

connecting the future

Technical Specifications

Windload @42 m/s N	60 N
Beamwidth horizontal °	35...40 °
Beamwidth vertical °	35...40 °
Bracketry	Mast bracket - rear
Main material	Aluminium
Weight (kg) TB(D) kg	1.2 kg
Colour	Black
Packaging	Brown box
Packing QTY	1
Product Length mm	720 mm
Product Width mm	610 mm
Packaging Height m	0.000 m
Packaging Width m	0.000 m
Packaging Depth m	0.000 m
Packaging Volume m3	0.000 m3
Net Weight kg	1.400 kg
Tara Weight kg	0.000 kg
Total Weight kg	1.400 kg