



HUB2KIT3MP(WHITE)/DD

Kit contains -

1 x HUB2

See page 2 for spec



2 x MOTIONPROTECT

See page 3 for spec



1 x KEYPAD

See page 4 for spec



1 x DOORPROTECT

See page 5 for spec



1 x STREETSIREN DD

See page 6 for spec



1 x HOMESIREN

See page 7 for spec



Hub 2 Specification

Complete set	The radio channel central unit with the support of visual alarm verification detectors
Installation	Indoors
Connected devices	100
Video surveillance support	Up to 25 cameras or DVRs
Users	50
Rooms	50
Security groups	9
MotionCam detector support	+
Communication channels	Ethernet Two 2G SIM-cards
Alarm signals	Delivery time: 0.15 sec Notification types: SMS, call, push-notification
Switching between the SIM-cards	4 minutes
CMS connectivity	Contact ID, SIA
The speed of alarm delivery to CMS	Instant
Software	OS Malevich
Power supply	Main supply: 110-240 V Battery backup: Li-Ion 2 A.h Up to 16 hours of offline operation when the Ethernet is switched off
Jeweller radio technology	Communication range with detectors - up to 2,000 in an open space Two-way communication between devices Operating frequencies - 868,0-868,6 Mhz Self-adjusting RF output power - up to 25 mW Black encryption based on AES algorithm Detector polling period - 12-300s Frequency hopping
Wings radio technology	Transmission of visual confirmations Delivery verification of packages
Operating temp range	From -10°C to +40°C
Size	163 x 163 x 36mm
Weight	362g
Complete set	Ajax Hub 2 intelligent control panel SmartBracket mounting panel Power cable, Ethernet cable, Installation kit, users guide
Connected ReX	5
Scenarios	32

MotionProtect Specification

Classification	Electro-optical combined radio channel security detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	PIR sensor
Alarm signal delivery time	0.15 s
Motion detection distance	Up to 12 m
Detection angles	Horizontal — 88.5°, Vertical — 80°
Sensitivity	Adjustable, 3 levels
Recommended installation height	2.4 m
Pet immunity	Weight — up to 20 kg, Height — up to 50 cm
Power supply	Battery: CR123A battery, Power supply voltage: 3 V Battery life — up to 7 years
Jeweller radio technology	Communication range with central unit — up to 1,700 m in an open space Two-way communication between devices Operating frequencies — 868.0—868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From +5°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	110x65x50 mm
Weight	86 g
Certification	Grade 2, CE
Complete set	MotionProtect motion detector SmartBracket mounting panel CR123A battery (pre-installed) Installation set User's guide

Keypad Specification

Classification	Radio channel touch keypad
Type of siren	Wireless, touch
Installation method	Indoors
Compatibility	Operates only with Hub, Hub Plus and ReX
Number of buttons	15
Duress code	Yes
Protection against password attack	Yes
Protection against passcode guessing	Yes
Arming/disarming indication	Yes
Power supply	Battery: AAA batteries Power supply voltage: 3 V Battery life — up to 2 years
Jeweller radio technology	Communication range with central unit — up to 1,700 m in an open space Two-way communication between devices Operating frequencies — 868.0-868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From -10°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	150x103x14mm
Weight	197 g
Certification	Grade 2, CE
Complete set	KeyPad touch keyboard SmartBracket mounting panel 4 AAA batteries (pre-installed) Installation set User's guide

Door Protect Specification

Classification	Point magnetic and contact radio channel security detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	Reed switch
Alarm signal delivery time	0.15 s
Activation threshold	Small magnet — 1 cm, Big magnet — 2 cm
Power supply	Battery: CR123A battery, Power supply voltage: 3 V Battery life — up to 7 years
Jeweller radio technology	Communication range with central unit — up to 1,200 m in an open space Two-way communication between devices Operating frequencies — 868.0—868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From +5°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	Diameter: 20 mm Height: 90 mm
Weight	29g
Certification	Grade 2, CE
Complete set	DoorProtect opening detector SmartBracket mounting panel Two magnets CR123A battery (pre-installed) External contact Installation set User's guide

Street Siren DD Specification

Classification	Warning device with LED indicators (outdoor siren)
Type of siren	Wireless
Installation method	Outdoors/Indoors
Compatibility	Operates only with Hub, Hub Plus, Hub 2 and ReX
Type of notification	Sound/light
Sound volume level	Adjustable, 85-113dB at a distance of 1m
Alarm duration	Adjustable, 3-180s
Indication of armed / disarmed status	Available
Power Supply	Battery: Four CR123A batteries, 3V Mains supply: DC 12 V±20%
Battery life	Up to 5 years
Jeweller radio tech	Communication range with central unit - up to 1500m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6MHz Self-adjusting RF output power - up to 25 mW Block encryption based on AES algorithm Detector polling period - 12-300s
Temperature sensor	Available
Operating temp range	From -25°C to +60°C
Permissible humidity	Up to 95%
Ingress protection rating	Ip54
Anti-sabotage	Forgery prevention Jamming detection Tamper-resistant
Remote config and testing	Available
Dimensions	200 x 200 x 51mm
Weight	528g
Complete set	StreetSiren DoubleDeck SmartBracket mounting panel Installation set Users guide

Home Siren Specification

Classification	Radio channel security sounder
Type of siren	Wireless
Installation method	Indoors
Type of notification	Sound
Connector for external LED	Available
Sound volume level	Adjustable, 81-105 dB at a distance of 1 m
Alarm length	Adjustable, 3-180 s
Indication of armed/ disarmed status	Yes
Alarm signal delivery time	0,15 s
Power supply	Battery: Two CR2 batteries Battery: Two CR123A batteries Power supply voltage: 3 V Battery life — up to 5 years
Jeweller radio technology	Communication range with central unit — up to 2,000 m in an open space Two-way communication between devices Operating frequencies — 868.0-868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From -10°C to +40°C
Permissible humidity	Up to 75%
Protection class of body	IP50
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	75x76x27mm
Weight	97 g
Certification	Grade 2, CE
Complete set	HomeSiren siren SmartBracket mounting panel Connector for LED indicator Two CR123A batteries (pre-installed) Installation set User's guide