

## TWT2 Wideband Tap H/V

Art. Number 307779



### TWT2 Wideband Tap H/V

The TWT2 tap is designed to be used with Wideband systems with Satellite IF frequencies from 290 MHz to 2340 MHz, and Terrestrial frequencies between 5 MHz and 862 MHz.

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702663077799

### FREQUENCY RANGE

Frequency range SAT | MHz 290...2340 MHz

Frequency range TER | MHz 5...862 MHz

### LOSS

Tap loss SAT | dB 11.0 dB

Tap loss TER | dB 13.0 dB

Through loss - Trunk SAT | dB 2.0 dB

Through loss - Trunk TER | dB 1.5...2.0 dB

### ELECTRICAL

Impedance |  $\Omega$  75  $\Omega$

### CONNECTORS

Number of inputs 3

Number of outputs 6

### MECHANICAL

Dimensions product (H x D x W) | mm 130x130x50 mm

Packing QTY 1

Product Height | mm 130 mm

Product Width | mm 130 mm



# TRIAx

connecting the future

## Technical Specifications

Product Depth   mm	50 mm
Packaging Height   m	0.055 m
Packaging Width   m	0.255 m
Packaging Depth   m	0.235 m
Packaging Volume   m <sup>3</sup>	0.003 m <sup>3</sup>
Net Weight   kg	0.250 kg
Tara Weight   kg	0.160 kg
Total Weight   kg	0.410 kg